

Product Brochure For W875

cs-55 - Circular Plunge & Mitre Cut Saw

55mm Depth Capacity
 Ø160mm Blade

Ex GST
\$270.00

Inc GST
\$297.00



ORDER CODE:	W875
MODEL:	cs-55
Type:	Circular Plunge Saw
Blade Diameter x Teeth (mm x T):	Ø160mm x 24T
Blade Thickness (mm):	2.4
Blade Bore (mm):	20
Blade Speed (rpm):	5500
Cut Depth @ 90° - Plunge Saw only (mm):	55
Cut Depth @ 45° - Plunge Saw only (mm):	41
Cut Depth @ 90° - with Guide Rail (mm):	~
Cut Depth @ 45° - with Guide Rail (mm):	~
Mitre Cutting Angle (deg):	0 - 45°
Closest to Wall Cutting (mm):	15.5
Dust Collector Connection Size (mm):	38
Voltage (V):	240
Motor Power (kW / hp):	1.2 / 1.6
Nett Weight (kg):	5.6



Description

The Scheppach circular plunge cut saw cs-55 – "Three Saws in One" can be used as a plunge saw, Portable hand saw & a Panel sizing saw, anyone can get great results in the shop or on the job site.

The combination of a Scheppach cs-55 parallel plunge saw with the "optional" guide rail allows the user to maintain a smooth and constant hand position while cutting 90° or 45° cuts.

Features

- German design & technology
- Powerful 1.2kW / 1.6hp 240V Motor
- Parallel plunge allows the user to maintain a smooth and constant hand position while cutting
- The enclosed guard gives a 90% dust extraction capability
- 55mm @ 90° maximum depth of cut allows the trimming and sizing of most common door sizes
- Can tilt saw head up to 45° and will cut 41mm maximum depth
- Maximum precision, even when cutting free hand
- 15.5mm – close to wall cutting is achievable with cs-55 saw
- Includes 24 tooth blade that gives a fine and accurate finish with very little breakout in laminates

Optional Accessories

- Replacement Saw Blades:
- 160 x 20 x 2.4mm 24 Teeth (W879)
- 160 x 20 x 2.2mm 48 Teeth (W880)

Product Brochure For W875


Specific Features



Shown with Optional Guide Rail



55mm maximum stepless cutting depth




Mitre cuts with stepless angle adjustment 0 to 45 Degree angle adjustment



Perfect for kitchen worktops - Shown with Optional Rail



Achieve cuts usually performed on a panel sizing table saw - Shown with Optional Rail



is55 ideal whatever the material solid natural timbers chipboard plywood even MDF and double coated boards



Ideal for edging up to 15.5mm from the wall



Saw in Up right Position - Shown with Optional Rail



Bottom View - Shown with Optional Rail

Product Brochure For W875

Recommended Accessories

W874

Circular Plunge & Mitre Cut Saw Package Deal




W876

Aluminium Guide Rail



W877

Guide Joiner, Clamps & Stop Accessory Kit



W8775

Heavy Duty Clamp Set



W878

Anti-Fall Over Saw Clamp



W879

Saw Blade - 160mm x 24T



W880

Saw Blade - 160mm x 48T



W885

Dust Collector

