

Product Brochure For S585T

PB-1030T - Hydraulic NC Panbrake - Ezy Touch Screen Control

3050 x 3.2mm Mild Steel Bending Capacity

Ex GST	Inc GST
\$21,500.00	\$23,650.00



ORDER CODE:	S585T
MODEL:	PB-1030T
Controller Type:	NC EZY Touch Screen & Multiple Program
Bending Length (mm):	3050
Mild Steel Capacity (mm):	3.2
Stainless Steel Capacity (mm):	1.6
Material Clamping Type:	Hydraulic Clamp
Material Bending Type:	Hydraulic Bend
Bending Angle Indicator (deg):	0-125°
Backgauge Travel (mm):	1000
Motor (kW / hp):	5.5 / 7.5
Voltage / Amperage (V / amp):	415
Floor Space (L x W x H) (mm):	3700 x 1540 x 1440
Nett Weight (kg):	3258



Description

The most recent edition to the Metalmaster Hydraulic NC Panbrake range now comes complete with a 7" colour touch screen control panel. The beauty of this Ezy-Touch screen design is it can store a massive 99 programs with 20 bend angles per program, and each bend angle allows you to fine-tune the material bend compensation. This feature simply removes the guesswork out and takes bending to the next level to achieve accuracy & repeatability every time. Another unique attribute built-in is a quick action head allowing adjusting for the different material thickness from 1mm to 3.2mm

The welded frame is constructed from heavy gauge steel for superior strength & minimal flex when operating under full capacity with extreme load. Metalmaster have thought outside the box when designing & manufacturing this machine as they have also made the clamp fingers extra long so you can bend up deep boxes or pans.

Features


- 3050mm x 3.2mm bending capacity
- Ezy-Touch NC Touch Screen Control features 99 programs, each program has up to 20 bends & each bend has material compensation. It also incorporates a quick bend function for jobbing work
- Auto cycle: after clamping bottom beam will bend to pre-set angle and return, head unclamps to set position
- Ezy-Touch NC programmable opening height & bending dwell timer ensures consistent bending angle
- Quick action rapid head adjustment to optimise bend radius on 1-3.2mm material thickness
- Heavy duty steel fabricated construction
- Roving foot pedal incorporates control panel for maximum flexibility
- High quality components ensure reliable performance for years of continuous operation
- Extended fingers allows bending of pans or boxes to a depth of 200mm
- Includes an adjustable rear manual backgauge, also adjustable for tapered material
- Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning:
 1. Panbrake bender is run & tested prior delivery
 2. Hydraulic oil is included with machine

Product Brochure For S585T


Specific Features



NC Ezytouch Control Panel



NC Ezytouch Program Page



NC Ezytouch Program Edit



NC Ezytouch Program List



NC Ezytouch Manual Program



Rapid Blade Adjustment for Material Thickness



Removable Fingers



Apron Safety Guards



Shown with Material Clamp Beam Open



Manual Backgauge



Roving Foot Pedal



Side View



Rear View



Shown with Optional Ball Transfer Tables - Order Code (L840)

Recommended Accessories

S581T
 Hydraulic NC Panbrake - Ezy
 Touch Screen Control

S584T
 Hydraulic NC Panbrake - Ezy
 Touch Screen Control

S586T
 Hydraulic NC Panbrake - Ezy
 Touch Screen Control

M800
 Rubber Mat - Anti-Fatigue



M805
 Rubber Mat - Anti-Fatigue

O000
 SpillFix Universal Organic
 Absorbent

O000A
 Natural Zeolite Absorbent

O043
 Rust & Corrosion Preventive -
 Penetrant & Lubrication



Product Brochure For S585T

sales@machineryhouse.com.au
www.machineryhouse.com.au

O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive - Penetrant & Lubrication



O044

Rust & Corrosion Preventive - Penetrant & Lubrication



O004

Superdraulic 46 Hydraulic Oil

