

**Product Brochure For B488** 

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

10-15

Inc GST

# B488 - Metal Band Saw Blade - 8-12TPI Bi-Metal, Blade - 3657 x 27 x 0.9mm

Suitable for Stainless Steel SUITS BMSO-320 Metal Cutting Band Saw



\$110.00 \$100.00 ORDER CODE: B488 Suits Band Saw Models: BMSO-320 Blade Size (L x W x T) (mm): 3657 x 27 x 0.9 Number of teeth per inch (TPI): 8-12 Blade Type: BI-METAL Blade Suitable for - Material Type: Mild & Stainless Steel

**Ex GST** 

Suits Section Size (mm):





#### Description

<b>Please Note:</b>

cb>Starrett Blades are distributed in Sydney & Brisbane
cb>Excision Blades are distributed in Melbourne & Perth

## IMPORTANT RUN-IN INSTRUCTIONS FOR BI-METAL BLADES

Avoid excessive feed pressure on run-in
Run-in at 3/4 normal feed pressure for first 25 square inches on tough material
After run-in, gradually increase feed to maximum cutting rate



**Product Brochure For B488** 

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

## **BLADE SELECTION CHARTS**

Band saw tooth size is determined by the size of the cross section to be cut. In general cutting thinner sections requires more teeth per inch, thicker sections require coarser pitches, or less teeth per inch.

To select an appropriate tooth size please refer to the table immediately below unless material to be cut is a tube, in which case refer to the larger table below. For general purpose cutting use a constant pitch blade, for more aggressive production cutting of harder to cut materials use a variable pitch blade.

## **SOLID SECTION**

Section Size (mm)	Constant Pitch (TPI)	Variable Pitch (TPI) 14/18 or 10/14			
Up to 10	24 or 18				
10-15	14	8-12 6-10 5-8			
16-30	10				
31-50	8				
51-80	6	4-6			
81-120	4	3-4			
121-200	3	2-3			
Over 200	2 or 1.25 1.4-2 or 0				



#### **TUBE SECTION**

Wall Thickness	Outside diameter of tube or maximum profile section length (mm)												
(mm)	20	40	60	80	100	120	150	200	300	500	600	700	800
2	14	14	14	14	14	14	10-14	10-14	8-12	8-12	6-10	5-8	5-8
3	14	14	10-14	10-14	10-14	10-14	8-12	8-12	6-10	6-10	5-8	5-8	5-8
4	14	14	10-14	10-14	8-12	8-12	6-10	6-10	5-8	5-8	4-6	4-6	4-6
5	14	10-14	10-14	8-12	8-12	6-10	6-10	5-8	5-8	4-6	4-6	4-6	4-6
6	14	10-14	10-14	8-12	8-12	6-10	6-10	5-8	5-8	4-6	4-6	3-4	3-4
8	14	10-14	8-12	8-12	6-10	6-10	5-8	5-8	4-6	4-6	3-4	3-4	3-4
10		8-12	8-12	6-10	6-10	5-8	5-8	4-6	4-6	3-4	3-4	3-4	3-4
12		8-12	6-10	6-10	5-8	5-8	4-6	4-6	3-4	3-4	3-4	3-4	2-3
15			6-10	5-8	5-8	4-6	4-6	4-6	3-4	3-4	3-4	2-3	2-3
20				5-8	4-6	4-6	4-6	3-4	3-4	2-3	2-3	2-3	2-3
30					4-6	4-6	3-4	3-4	3-4	2-3	2-3	2-3	2-3
50						3-4	3-4	3-4	2-3	2-3	2-3	2-3	2-3
75							2-3	2-3	2-3	2-3	2-3	1.4-2	1.4-2