

CHV-200V - Safeway Compact Hydraulic Vice

200mm Jaw Width
 280mm Jaw Opening

Back In Stock Soon

Ex GST **Inc GST**
\$2,690.00 **\$2,959.00**



ORDER CODE:	V323
MODEL:	CHV-200V
Jaw Width (mm):	200
D - Jaw Width (mm):	201
J - Jaw Opening (mm):	280
J1 - Jaw Opening with Optional Jaws (mm):	280 - 360
J2 - Jaw Opening with Optional Jaws (mm):	280 - 420
J3 - Jaw Opening with Optional Jaws (mm):	280 - 540
K - Jaw Height (mm):	63
Pressure (kgf):	7000
A (mm):	705
B (mm):	570
C (mm):	135
E (mm):	170
F (mm):	173
G (mm):	90
H (mm):	18
I (mm):	150
L (mm):	22
M (mm):	125
N (mm):	18
P (mm):	14
X (mm):	82
Y (mm):	110
Nett Weight (kg):	80



Description









Safeway Precision 200mm Compact Hydraulic Vice for use where precise work holding is required in a restricted space.

Features


- Precision ground on all surfaces
- Flame-hardened bed to HRC 45
- Semi-sphere to eliminate jaw lift
- Swarf covers over leadscrew
- Toleranced for use as matched pairs

Product Brochure For V323

sales@machineryhouse.com.au
 www.machineryhouse.com.au

NO	TEST REPORT	JIS grade 1.	GUARANTEED		
1	Both jaw plate parallel	0.020 100mm	0.020 100mm		
2	Keyways on bottom of vise bed square to clamping surface of jaw plate.	0.020 100mm	0.015 100mm		
3	Vise side-lock on bottom to slide way square.	0.020 100mm	0.010 100mm		
4	Surface of vise bed parallel to bottom of vise body.	0.020 100mm	0.010 100mm		
5	Top of rectangular test block clamped tightly by jaw parallel to bottom of vise body	0.030 100mm	0.020 100mm		
6	Max. opening test block parallel to bottom of vise body.	0.050 100mm	0.030 100mm		

Specific Features



Insert

Recommended Accessories

V3218
 Safeway End Mount Hardened Jaws - 200mm

V3213
 Safeway Serrated Hardened Jaws - 200mm

V3209
 Safeway Vee Hardened Jaw - 200mm

