

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au

www.machineryhouse.com.au

Product Brochure For S135B

S135B - HSS + COBALT Cold Saw Blade

Ø315mm / 40mm Bore - 180T Suitable for Stainless Steel

Ex GST Inc GST

\$310.00	\$341.00
ORDER CODE:	S135B
Туре:	HSS with COBALT
Blade Diameter (mm):	315
Blade Thickness (mm):	2.5
Bore Diameter (mm):	40
Number Of Teeth (No.):	180
Blade Best Suited for - Material Type:	Mild & Stainless Steel





Description

Made in Italy from highest quality High Speed Steel

Made in Italy

Features

• Quality European Blades



Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

Product Brochure For S135B

sales@machineryhouse.com.au www.machineryhouse.com.au

BLADE SELECTION CHARTS

Coldsaw blade tooth size is determined by the size of the cross section to be cut. In general cutting thinner sections requires more teeth, thicker sections require less teeth.

To select an appropriate tooth size please refer to the table immediately below unless material to be cut is a tube, in which case refer to the larger table below.

Solid Material Blade Selection Chart

Material Diameter	Blade Diameter (mm)			
	300	315 Number	350 of teeth	400
10mm	280	280	280	300
20mm	160	160	200	240
30mm	140	140	160	200
40mm	120	120	140	140
50mm	80	80	100	120
60mm	x	x	80	100

Hollow Tube Blade Selection Chart

Material Outside Diameter	Wall Thickness	Blade Diameter (mm)				
		300	315	350	400	
Diameter			Number of teeth			
20mm	3 2 1	180 240 300	180 240 320	220 280 350	240 340 400	
40mm	4 3 2 1	140 160 220 300	140 160 220 320	160 180 260 350	180 200 280 400	
50mm	5 4 3 2 1	120 140 160 220 300	140 160 180 220 320	160 180 200 280 350	180 200 220 300 400	
80mm	5 4 3 2 1	140 160 180 200 280	140 160 200 240 300	160 180 200 220 320	160 180 220 240 360	
100mm	5 4 3 2 1	× × × × × ×	140 160 200 220 300	120 140 180 200 300	140 160 180 220 340	
120mm	5 4 3 2 1	× × × × ×	× × × × × × ×	120 160 180 200 300	140 160 180 220 340	