

Product Brochure For C4610

Powermax45 XP - Plasma Cutter

Clean Cut 16 mm - Cut Speed 500 mm/min / 22 mm - Cut Speed 250 mm/min
 Severance (hand cutting) 29mm - Cut Speed 125 mm/min



Special Order

Ex GST	Inc GST
\$4,225.00	\$4,647.50

ORDER CODE:	C4610
MODEL:	Powermax45 XP
Part Number:	~
Cutting Capacity - Steel (mm):	22 mm @ 250 mm/min
Cutting Capacity - Aluminium (mm):	~
Voltage / Amperage (V / amp):	240 / 33
Recommended Plug (amp):	32
Duty Cycle:	50% @ 45Amps
Current Range (amp):	10-45
Air Pressure Required (PSI):	90
Air Flow Capacity Required (L/min /Bar):	188 / 5.9
Recommended Generator KVA (kVA):	12.5
Dimensions (mm):	442 x 173 x 357
Nett Weight (kg):	15



Description

The Powermax45® XP delivers increased cut capacity, as well as faster cut speeds, and automatic gas adjustment for quick, simple setup and operation. Duramax® Lock torches support handheld and mechanized cutting of a wider range of metal thicknesses, along with precision gouging such as spot weld removal, and marking capabilities

Features

- Small size and light weight provide exceptional portability for a 16mm / 22mm rated cutting system
- Patented drag-cutting technology makes the Powermax45 XP easy to use – even for first-time operators
- Smart Sense™ technology ensures that air pressure is always correctly set
- A wide range of torch and consumable styles to choose from for both handheld and automated processes
- Extensive array of application capabilities via specialty consumables for fine feature cutting, extended reach cutting, gouging, precision gouging, and marking

Includes

- Powermax 45 XP Power Source
- 6.1 metre Duramax Lock 75° Plasma Torch
- 6.1 metre Earth Lead
- Instruction Manual

Product Brochure For C4610

Specific Features



Powermax 45XP In Use

Recommended Accessories


P8062
 Plasma Hand Torch



P8453
 Hypertherm 45XP/65/85/105
 Shield Max Control Gouging



P8454
 Hypertherm 45 Shield Precision
 Gouging




P8451
 Hypertherm 10-20A Shield



P848
 Hypertherm 65-105A Retaining
 Cap



P8382
 Hypertherm 45XP Nozzle Max
 Control Gouging



P8381
 Hypertherm 10-25A Nozzle
 Marking/Gouging



P837
 Hypertherm 30-105A Electrode



Product Brochure For C4610

P843
 Hypertherm 45-85A Swirl Ring



P8482
 Hypertherm 45XP/65/85/105
 Retaining Cap HyAccess



P8383
 Hypertherm 45XP/65/85/105
 Nozzle HyAccess



P8384
 Hypertherm 45XP/65/85/105
 Nozzle HyAccess Gouging



P8372
 Hypertherm 45XP/65/85/105
 Electrode HyAccess



P8385
 Hypertherm 45XP/65/85/105
 Nozzle-Shield FlushCut



P8373
 Hypertherm 45XP/65/85
 Electrode FlushCut



P8432
 Hypertherm 45XP/65/85 Swirl
 Ring FlushCut



P8452
 Hypertherm Shield Drag Cutting
 Suits Hand Torch



P838
 Hypertherm 45A Nozzle



P8371
 Hypertherm 45-105A Copper
 Plus Electrode



P8472
 Hypertherm Deflector Suits
 Hand Torch



Product Brochure For C4610

sales@machineryhouse.com.au
www.machineryhouse.com.au

P842

Hypertherm FineCut Only
Nozzle



P8431

Hypertherm Swirl Ring Finecut
Suits Hand Torch

