

**Product Brochure For S158S** 

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

240

Mild & Stainless Steel

Inc GST

## S158S - HSS + COBALT Cold Saw Blade

Ø315mm / 32mm Bore - 240T Suitable for Stainless Steel



\$310.00 \$341.00 ORDER CODE: S158S HSS with COBALT Type: Blade Diameter (mm): 315 Blade Thickness (mm): 2.5 Bore Diameter (mm): 32

**Ex GST** 

Number Of Teeth (No.):

Blade Best Suited for - Material Type:







### Description

Made in Italy from highest quality High Speed Steel

#### **Features**

- Quality European blades suitable for cutting Mild Steels, Structural Steels, Stainless Steels, Aluminium, Alloys, Copper, Brass. Long lasting high wear resistance Can be resharpened



**Product Brochure For S158S** 

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

# **BLADE SELECTION CHARTS**

Coldsaw blade tooth size is determined by the size of the cross section to be cut. In general cutting thinner sections requires more teeth, thicker sections require less teeth.

To select an appropriate tooth size please refer to the table immediately below unless material to be cut is a tube, in which case refer to the larger table below.

### Solid Material Blade Selection Chart

Material Diameter	Blade Diameter (mm)					
	300	315 Number	350 of teeth	400		
10mm	280	280	280	300		
20mm	160	160	200	240		
30mm	140	140	160	200		
40mm	120	120	140	140		
50mm	80	80	100	120		
60mm	×	×	80	100		

### **Hollow Tube Blade Selection Chart**

Material Outside	Wall Thickness	Blade Diameter (mm)				
		300	315	350	400	
Diameter		Number of teeth				
20mm	3	180	180	220	240	
Sales Propagations	3 2 1	240 300	240 320	280 350	340 400	
W W W W W W W W W W W W W W W W W W W		300	320	350	400	
40mm	4	140	140	160	180	
	3	160 220	160 220	180 260	200 280	
	3 2 1	300	320	350	400	
	0		020			
50mm	5 4 3 2 1	120	140	160	180	
	4 3	140 160	160 180	180 200	200 220	
	2	220	220	280	300	
	1	300	320	350	400	
80mm	5	140	140	160	160	
ADMICTROS STOLES	4	160	160	180	180	
	3	180	200	200	220	
	5 4 3 2 1	200 280	240 300	220 320	240 360	
		200	000	020	000	
100mm	5	×	140	120	140	
	5 4 3 2 1	×	160 200	140 180	160	
	3	X X	220	200	180 220	
	ī	x	300	300	340	
120mm	5	×	×	120	140	
10/3/580/59/5/00	4	×	×	160	160	
	3	×	×	180	180	
	5 4 3 2 1	×	×	200 300	220 340	
		_ ^		000	040	