

Product Brochure For W382

WL-18 - Swivel Head Wood Lathe

Ø310mm Swing x 900mm Between Centres
 Variable Speed 500 ~ 2000rpm & Swivelling Headstock

Ex GST
\$720.00

Inc GST
\$792.00



ORDER CODE:	W382
MODEL:	WL-18
Swing Over Bed (mm):	310
Between Centres (mm):	900
Spindle Nose Thread:	1" x 10TPI
Spindle Nose Taper (MT):	2
Spindle Speeds (rpm):	Variable 500 - 2000
Tailstock Taper (MT):	2
Motor Power (kW / hp):	0.75 / 1
Voltage / Amperage (V / amp):	240 / 10
Floor Space (W x D x H) (mm):	1610 x 650 x 1120
Floor Space With Option Stand (W x D x H) (mm):	-
Nett Weight (kg):	85



Description

The WL-18 wood lathe is an excellent "value for money" floor standing lathe, perfect for getting the green wood turner started in the craft with a minimum of outlay.

The WL-18 lathe is mainly made up from cast iron to provide the rigidity that's required and needed in all good wood lathes. Changing the spindle speed from 500 to 2000rpm is extremely easy via the stepless variable speed control lever mounted on the front of the head. The headstock can be swivelled and locked in position to allow bowls to be turned in front of the lathe; the 45° and 90° positions are indexed for ease of selection.

The lathe comes complete with an outboard tool rest extension which is used to get the bowl rest into the best position when turning with the head rotated. The head and tailstock both have 2 morse tapers and the drive spindle thread is a common 1" x 10tpi. Supplied as standard with the machine is a 4 prong drive centre, revolving tailstock centre & faceplate.

Features

- Cast iron construction, bed, head and tailstock
- Variable speed control 500-2000rpm
- Swivelling headstock can be locked in position
- Outboard tool rest extension
- Dust proof magnetic switch
- Headstock and tailstock have 2 Morse tapers, 1" x 10tpi spindle thread

Includes

- Bowl turning attachment
- Faceplate
- Drive & live centres
- Tool rest
- Stand

Product Brochure For W382

Specific Features



Headstock



Headstock Left View



Swivel Head Release Lock



Swivel Headstock



Variable Speed Lever



Faceplate

SPINDLE SPEED RANGE (rpm)	
1 - 500	6 - 1210
2 - 620	7 - 1400
3 - 760	8 - 1590
4 - 900	9 - 1790
5 - 1050	10 - 2000


Spindle Speeds



Bowl Turning Setup Right View



Shown Set Up with Bowl



Outrigger Table For Bowl Attachment



Standard Tool Rest



Outrigger Tool Rest



Tailstock



Switch On Off



Included Parts



Drive Centre

Product Brochure For W382



Front View

Left View

Rear View

Rear Left View

Recommended Accessories

W295

Curved Tool Rest Set



W300

Carbide Wood Turning Tools - 6 Piece Set



W301

HSS Wood Turning Tools - 8 Piece Set



W302

HSS Wood Turning Tools - 6 Piece Set



W305

Bowl Sanding Tool



W378

Roller Steady



D442A

2MT x JT3 Drill Chuck Arbor



C290

Heavy Duty Drill Chuck - Keyed Type




Product Brochure For W382

W370
 Scroll Chuck -100mm



W375
 Scroll Chuck Accessory Kit



W297
 Face Plate



W298
 Face Plate



W306
 Pen Mandrel Set - 2MT



W3665
 Scroll Chuck Insert - 1" x 10TPI



R8197
 Scroll Chuck - 90mm - with
 Bonus 50mm Face Plate Ring



R8175
 Scroll Chuck - 100mm - with
 Bonus 50mm Face Plate Ring



W338B
 Wood Lathe - Dust Chute - Big
 Gulp

