

TU-3008G-20M - Opti-Turn Lathe & Mill Drill Combination Package Deal

300 x 700mm
 Included BF-20AV Mill Head



OPTIMUM



Package Deal

Ex GST Inc GST
\$4,700.00 \$5,170.00

Package Contents - SAVE \$264.00 (Inc)

1 x L691 - TU-3008G Opti-Turn Bench Lathe	\$4,279.00
1 x M647 - BF-20AV Opti-Mill Head Attachment - Geared Head	\$1,155.00
Normal Price (Inc):	\$5,434.00

ORDER CODE:	K149
MODEL:	TU-3008G-20M
KIT Includes:	TU-3008G & BF-20AV
Lathe Specifications:	LATHE SPECIFICATIONS
Tool Height To Suit (mm):	16
Distance Between Centres (mm):	700
Swing Over Bed (mm):	300
Swing Over Cross Slide (mm):	190
Centre Height (mm):	150
Spindle Bore (mm):	38
Spindle Nose Type:	D1-4
Bed Width (mm):	180
Headstock Taper (MT):	5
Tailstock Taper (MT):	3
Cross Slide Travel (mm):	150
Compound Slide Travel (mm):	65
Leadscrew:	Metric
Longitudinal Feed (Z-Axis) (mm/rev):	0.085 - 0.83
Cross Feed (X-Axis):	0.01 ~0.10
Metric Thread Range (mm):	0.2 - 3.5
Imperial Thread Range (TPI):	8 - 56"
Three Jaw Chuck Size (mm):	160
Four Jaw Chuck Size:	Optional
Spindle Speeds (No. / rpm):	12 (125 - 2400)
Motor Power - Lathe (kW / hp):	1.5 / 2
Voltage / Amperage - Lathe (V / amp):	240 / 10
Mill Specifications:	MILL SPECIFICATIONS
Spindle Taper (MT):	3
Column Type:	Dovetail
Swivel Head (Left ~ Right) (± Deg):	±90
Vertical Travel (Z-Axis) (mm):	280
Drilling Capacity (mm):	16
End Milling Capacity (mm):	20
Face Milling Capacity (mm):	63
Spindle Speeds Vertical (No. / rpm):	Variable (90-3000)
Motor Power - Mill (kW / hp):	0.85 / 1.13
Voltage / Amperage - Mill (V / amp):	240 / 10
Nett Weight (kg):	383

Description

TU-3008G-20M Combination Lathe & Mill-Drill consist of TU-3008G bench lathe & BF-20AV mill head

This new TU-3008G model geared head lathe of very modern design has many convenient facilities ideal for the enthusiastic model engineer for small component manufacturer. A very rigid 180mm cast iron bed width, induction hardened and ground slideways gives a high level of precision turning. The lathe capacity is 700mm between the centres and 300mm swing over the bed and with a generous 38mm spindle bore allowing larger stock to be placed through the headstock. The workhorse that drives this lathe has an upgraded powerful 2hp (1.5kW) motor providing smooth running.

Product Brochure For K149

Other very useful features included are cross and longitudinal power feeds that's not normally found of small conventional lathes, quick lock tailstock and both metric and imperial thread cutting, ranging from 8-56 tpi or 0.2-3.5mm pitch. Also included are a 4-way indexing tool post with 16mm tool shank capacity, fine adjustment on the tailstock for taper turning and the rear splash guard. A 160mm 3-jaw chuck with reverse jaws is also supplied.

Features

- LATHE: TU-3008G
 - Geared headstock for quick change of 12 spindle speeds 125-2400rpm
 - Ribbed prism bed made of grey cast iron
 - Inductively hardened and ground bed guideways
 - Automatic cross & longitudinal power feeds
 - Spindle nose accuracy 0.009mm
 - 3 Jaw chuck running accuracy 0.04mm
 - D1-4 camlock spindle for quick chuck changes
 - Forward & reverse spindle direction switch
 - Oils sight glass on head-stock & gearbox
 - Change gears for metric and imperial thread cutting
 - Enclosed feed and threading gearbox
 - Belt cover with tamper proof safety micro switch
 - Heavy duty rotating safety chuck guard with micro switch
 - Sliding tool post safety guard
 - Cross slide and bed length designed to adapt Optimum DRO scales
-
- MILL: BF-20AV
 - Electronic infinitely variable speed
 - 3MT spindle taper
 - Dovetail vertical Z-Axis
 - Digital readout speed display
 - Work light mounted underneath mill head
 - Digital depth display with zero reset for quill
 - Tilting head to $\pm 90^\circ$ from vertical
 - 2 speed gearbox (high / low) drive
 - Forward and reverse spindle switch
 - Scale collars for all Axis are adjustable
 - Adjustable dovetail slideway on Z-Axis
 - Adjustable drill length stop
 - Metric dial graduations
- Note: The lathe rear splash tray is required to be removed to fit Mill Head Attachment.

Includes

- LATHE: TU-3008G
 - 160mm 3 jaw chuck with reverse jaws
 - Change gears for metric & Imperial thread cutting
 - Chuck guard
 - Toolpost guard
 - 2 dead centres
 - 3-jaw chuck with reversible jaws
 - Swarf drip tray
 - Rear splash guard
-
- MILL: BF-20AV
 - 3MT x JT6 drill chuck arbor
 - Safety cutter guard
 - Bracket kit for optional digital readout.

Product Brochure For K149

Specific Features



Front View



Left View



Right View with Mill Table Ready



Front View with Mill Table Ready



Left View with Mill Table Ready



Front View with Mill Head Tilted



Right View with Mill Head Tilted



Mill Head Rear View



Mill Head Left View



Mill Head Right View



Shown on Optional Stand Right View



Shown on Optional Stand Front View



Shown on Optional Stand Left View



Shown on Optional Stand with Mill Table Ready



Shown on Optional Stand with Mill Table Ready Front View



Shown on Optional Stand with Mill Table Ready Left View

Product Brochure For K149



Shown on Optional Stand with Mill Table Ready Rear View



Stand Sold Separately
Lathe



Top View



Front View



Shown with Optional Stand L690 Top View



Shown with Optional Stand L690 Left View



Safety Chuck Guard



Safety Chuck Guard Open Position




Headstock Controls



Spindle Speed Levers and Speed Chart



Headstock Controls



Top View Saddle and Chuck




Spindle Direction and Emergency Stop Switches



On Off Switch




Through Spindle




4 Way Toolpost


Product Brochure For K149




Saddle Left View




Saddle Front View




Saddle Right View




Saddle Rear View




Safety Cutter Guard Left



Safety Cutter Guard Right




Safety Cutter Guard Tilted Down



Feed and Thread Engagement Levers




Swivel Compound Slide



Thread Chasing Dial



Saddle Handwheel Graduations




Compound Slide Hand Wheel



Cross Feed Hand Wheel Graduations



Tailstock



Tailstock Quill Graduations




Tailstock Horizontal Adjustment


Product Brochure For K149




Tailstock Hand Wheel




Ground and Hardened Bed



Slides Ready For Mounting of DRO Scales



Mounting Point for Optional Milling Head



Change Gears



Parts Included



Mill Head



Safety Cutter Guard



Digital Readout For Quill Depth



Control Panel



Quill Fine Adjustment



Drawbar



Quill Handle



High Low Handle



Head Height Scale



Head Height Adjustment Handle

Product Brochure For K149



Tilt Head Adjustment



Dovetail Column



Light

Recommended Accessories

L690
 Lathe Stand

C252
 4 Jaw Independent Lathe Chuck

L6917
 Lathe Steady - Travelling

L6916
 Lathe Steady - Fixed



D695
 3-Axis Optimum Digital Readout Counter - 1µm

D694
 1500mm Optimum Magnetic Digital Readout Scale

L017
 Right Hand Turning Tool Holder

L018
 Left Hand Turning Tool Holder



Product Brochure For K149

L0077

Lathe Turning Tool Kit - 7 piece
Insert Type



L451

Lathe Turning Tool Kit - 3 piece
Insert Type



L457

Lathe Threading Tool Kit - Insert
Type




L465

Professional Lathe Parting Tool
Kit - Insert Type



C0945

Clamp Kit 58 piece - Workshop
Series



D442A

2MT x JT3 Drill Chuck Arbor



D1272

Metric Precision HSS Drill Set -
25 Piece



D1282

Imperial Precision HSS Drill Set
- 29 Piece



D126

Metric Precision HSS Drill Set -
170 Pieces



C050

2MT Live Centre



L076

Knurling Tool Holder Kit




P235

Coolant Pump & Tank




Product Brochure For K149

L341
Fitting and Machining Technical Book



L3455
Professional Sheet Metal Fabrication Book



L280
Quick Change Toolpost



L280A
Quick Change Toolpost Holder - Std



L277
Vertical Mill Slide



M9991
Magnetic Floor Sweeper




L300
Magnetic Swarf Remover



M800
Rubber Mat - Anti-Fatigue



M805
Rubber Mat - Anti-Fatigue



S090A
Soluble Metal Cutting Fluid - 1 Litre



S090
Soluble Metal Cutting Fluid - 5 Litre



S076
Cutting Tool Lubricant Fluid - 500ml



Product Brochure For K149

S077

Drilling, Tapping & Cutting Tool
 Lubricant Spray - 400g



S075

Cutting Tool Lubricant Paste -
 200g



S074

Cutting Tool Lubricant Paste -
 500g



D7142

2-Axis Digital Readout Counter -
 1µm or 5µm



D720C

200mm Easson Digital Readout
 Scale



D728

600mm Easson Digital Readout
 Scale



C134

3MT Collet



C926

Collet & Chuck Set - 20 Piece



C922B

Collet & Chuck Set - 8 Piece



C090

Clamp Kit 58 piece - Workshop
 Series



C0948

Mini Clamp Kit 10 piece -
 Workshop Series



M3301

Metric HSS Slot Drill & End Mill
 Set - 10 Piece



Product Brochure For K149

M3321
 Imperial HSS Slot Drill & End Mill Set - 10 Piece



M182
 Precision Boring Head Kit



M192
 Boring Head Shank



M180
 Boring Bar Set - 9 piece



M250
 Parallel Set - 8 Piece



M530
 Universal Milling Kit - 4 Piece




M528
 Face Mill 90° - Positive Rake



L066
 KYOCERA Carbide Inserts - Milling



V004
 Cast Iron Vee Block



R001
 Rotary Table



R005
 Vertex Rotary Table



R0014
 Tilting Rotary Table



Product Brochure For K149

O000

SpillFix Universal Organic Absorbent



O000A

Natural Zeolite Absorbent



O043

Rust & Corrosion Preventive - Penetrant & Lubrication



O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive - Penetrant & Lubrication



O044

Rust & Corrosion Preventive - Penetrant & Lubrication

