

Product Brochure For S117A

TNF-115 - Non-Ferrous Metal Cutting Saw - Swivel & Compound Mitre Head

Ø400mm Blade, 108 x 195mm Rectangle Capacity
 Includes 1 x 3 Metre Infeed & 1 x 3 Metre Outfeed Roller Conveyors
 with Adjustable Stop System

Ex GST **Inc GST**
\$7,800.00 **\$8,580.00**



ORDER CODE:	S117A
MODEL:	TNF-115
Cutting Head Action (Auto-Manual):	Manual
Operation Type:	Swivel - Dual Mitre & Compound Left
Round Capacity @ 90° / 45° (mm):	108 / 108
Square Capacity @ 90° / 45° (mm):	108 / 108
Rectangle Capacity @ 90° / 45° (mm):	108 x 195 / 108 x 138
Compound Rectangle Capacity @ 45° x 45° (mm):	70 x 138
Compound Square Capacity @ 45° x 45° (mm):	70 x 70
Blade Size (D x B x T) (mm):	Ø400
Number of Teeth (No.):	~
Vice Clamping Fixture:	Pneumatic
Coolant System:	Spray Mist
Table Working Height (with Stand) (mm):	950
Blade Speeds (rpm):	4800
Motor Power (kW / hp):	1.5 / 2
Voltage (V):	415
Machine Dimension (mm):	6570 x 780 x 1570
Nett Weight (kg):	140



Description

Brobo - Aluminium Saw
 ALUMINIUM & PVC PROFILE CUTTING

Features

- Mitering 45° left, straight 90° and 45° right with rapid adjustment bumpers
- 45° Compound Mitering
- Vertical and horizontal pneumatic clamping
- 400mm TCT blade
- 3m Adjustable length stop
- Trigger Switch (DMT) to activate the machine

Includes

- 3 metre Infeed roller conveyors
- 3 metre outfeed roller conveyor
- 3 metre adjustable length stop

Product Brochure For S117A

Specific Features



Left View



Right View



Side View

Recommended Accessories

S070

Metalium Spray Oil TCT ALU - 5 Litre




M800

Rubber Mat - Anti-Fatigue



M805

Rubber Mat - Anti-Fatigue



O000

SpillFix Universal Organic Absorbent



O000A

Natural Zeolite Absorbent



O043

Rust & Corrosion Preventive - Penetrant & Lubricant



O042

General Purpose Lubricant & Corrosion Inhibitor



O040

Rust & Corrosion Preventive - Penetrant & Lubricant



Product Brochure For S117A

sales@machineryhouse.com.au
www.machineryhouse.com.au

O044

Rust & Corrosion Preventive -
Penetrant & Lubrication

