

D737 - 1200mm Easson Digital Readout Scales

VS10 Standard Scale
 5µm Resolution

Ex GST
\$400.00

Inc GST
\$440.00



ORDER CODE:	D737
Type:	VS10 Standard Scale
Travel - Maximum (mm):	1200
Overall Length (L) (mm):	1346
Scale Resolution (µm):	5
Scale Accuracy (µm):	±10
Cable Length (Metre):	5
Backing Support Plate (Yes / No):	No
Width x Height (W x H) (mm):	27.5 x 33.5



Description

Easson VS series Glass Grating Linear Transducer: EASSON - Always committed to Quality, Technology & Innovation

Features

- **DOUBLE SEAL DESIGNED SCALES:**
- The plastic seals of the transducer use an innovative material to offer superior oil resistance, high elastic recovery properties and durability, carefully designed lip geometry offer low slide resistance.
- **100% LASER CALIBRATION:**
- All glass grating transducers are individually inspected and calibrated by our in-house laser calibrator to ensure accuracy complies 100% with the specifications.
- **ADVANCED OPTICAL MEASURING SYSTEM:**
- The slide carrier of the VS series scales, use a five bearing design for optical grating linear transducer which has been proven as the most reliable system design in today's market.
- The glass grating slide-ways are lapped, and JIS standard P5 grade bearings are used to achieve smooth and accurate movement and long working life.
- **D.I.Y. INSTALLATION:**
- An easy-to-follow D.I.Y. Installation Manual is supplied with each system, complete with illustrations and mounting brackets.

MODEL		VS 10	
Measuring Standard	Glass scale - Grating		
Optical Detecting System	Transmissive Infrared		
Slide Carrier System	Vertical five bearing supporting system	45° support	
Resolution	5µm		
Measurement Travel (100-1200mm)	Every 50mm per length specification		
Measurement Travel (1300-3000mm)	-		Every length
Accuracy (100-450mm) Accuracy (500-1000mm) Accuracy (1050-1250mm) Accuracy (1300-3000mm)	±3 - ±5µm ±10µm ±10µm -		
Repeatability	2µm		
Hysteresis	3µm		
Protection	DIN		
Power Supply	DC		
Output Signals			

Product Brochure For D737

Specific Features



DSub9 Male Plug

Dsub 9
9 pin male connector plug

Pin	TTL Signal	422A Signal	Cable Color
1	—	A	Yellow
2	0V	0V	White
3	—	B	Red
4	Ground	0V	Ground
5	—	R	Black
6	A	A	Green
7	5V	5V	Brown
8	B	B	Blue
9	R	R	Gray

Dsub9 Wiring Diagram



DIY Installation



Parts



Close Up

Recommended Accessories

D7142
2-Axis Digital Readout Counter - 1µm or 5µm

D7143
3-Axis Digital Readout Counter - 1µm or 5µm

D709
Easson Scales - Extension Cable

D710
Easson Scales - Extension Cable



Product Brochure For D737

sales@machineryhouse.com.au
www.machineryhouse.com.au

D770
Digital Readout Mounting
Bracket Kit



D772
Digital Readout Scale Mounting
Bracket Kit



D711
Adaptor Cable



D712
Adaptor Cable