

Product Brochure For G062

P3 powerlube® - Air Operated - Grease Gun

Suits 20kg Drum

Ex GST	Inc GST
\$1,200.00	\$1,320.00

ORDER CODE:	G062
MODEL:	P3 powerlube®
Type:	Air Operated & Grease Gun
Size:	20kg Drum



Description

The P3 POWERLUBE® is the ultimate in high pressure, air-powered greasing. With models available to suit containers from 12.5kg (28 lbs.) to 20 kg (48 lbs.), it is fitted with a 50:1 ratio air motor which can run off most small compressors to provide fast, continuous greasing. The P3 POWERLUBE is also suitable for underground coal mine applications.

Features

- Quiet, non-corroding air motor
- Grease viscosity: up to NLGI No.2
- Wetted components: zinc and hard chrome plated carbon steel, brass, and nitrile and polyurethane rubber
- Output: approx. 460 g/min (16 oz/min)
- Max. air pressure: 1,030 kPa (150 psi, 10.3 bar)
- Min. air pressure: 400 kPa (60 psi, 4 bar)
- Min. compressor size: 0.08 m³/min (3 cfm)
- Air inlet/fluid outlet: ¼" NPT (F)
- Pump ratio: 50:1 (grease pressure is 50 times air)
- B2 gun pressure: up to 69,000 kPa (10,000 psi, 690 bar) (boost pressure)
- Hose thread: ¼" NPT (M) TA-7K Filter & Regulator Kit
- Low air consumption
- No air line lubricator required
- Rubber edged follower plate
- 4m (13 ft.) x 6 mm (¼") ID delivery hose
- B2 booster gun with 360° ZSB swivel
- Fully serviceable
- 10 Year Macnaught Warranty

Optional Accessories

- TR5 Trolley
- PDF13 Push On Extension
- PDF21 Push On Extension
- TA-7K Filter & Regulator Kit
- KZDXL Straight Needlepoint Coupler
- KRV Pressure Release Valve

