

Product Brochure For S138E

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Mild Steel

Inc GST

S138E - HSS Cold Saw Blade

Ø400mm / 40mm Bore - 240T



\$390.00	\$429.00	
ORDER CODE:		S138E
Туре:		HSS
Blade Diameter (mm):		400
Blade Thickness (mm):		3
Bore Diameter (mm):		40
Number Of Teeth (No.):		240

Ex GST

Blade Best Suited for - Material Type:







Description

Made in Italy from highest quality High Speed Steel

Features

- Quality European blades suitable for cutting Mild Steels, Structural Steels, Stainless Steels, Aluminium, Alloys, Copper, Brass. Long lasting high wear resistance Can be resharpened



Product Brochure For S138E

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

BLADE SELECTION CHARTS

Coldsaw blade tooth size is determined by the size of the cross section to be cut. In general cutting thinner sections requires more teeth, thicker sections require less teeth.

To select an appropriate tooth size please refer to the table immediately below unless material to be cut is a tube, in which case refer to the larger table below.

Solid Material Blade Selection Chart

Material Diameter		Blade Diar	neter (mm)	
	300	315 Number	350 of teeth	400
10mm	280	280	280	300
20mm	160	160	200	240
30mm	140	140	160	200
40mm	120	120	140	140
50mm	80	80	100	120
60mm	×	×	80	100

Hollow Tube Blade Selection Chart

Material	Wall Thickness		Blade Diameter (mm)			
Outside Diameter		300 315 350 400 Number of teeth				
20mm	3	180	180	220	240	
	2	240	240	280	340	
	1	300	320	350	400	
40mm	4	140	140	160	180	
	3	160	160	180	200	
	2	220	220	260	280	
	1	300	320	350	400	
50mm	5	120	140	160	180	
	4	140	160	180	200	
	3	160	180	200	220	
	2	220	220	280	300	
	1	300	320	350	400	
80mm	5	140	140	160	160	
	4	160	160	180	180	
	3	180	200	200	220	
	2	200	240	220	240	
	1	280	300	320	360	
100mm	5 4 3 2 1	x x x x	140 160 200 220 300	120 140 180 200 300	140 160 180 220 340	
120mm	5 4 3 2 1	x x x x	× × × ×	120 160 180 200 300	140 160 180 220 340	