

Product Brochure For S139B

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

180

Mild & Stainless Steel

Inc GST

S139B - HSS + COBALT Cold Saw Blade

Ø400mm / 40mm Bore - 180T Suitable for Stainless Steel



\$500.00 \$550.00 ORDER CODE: S139B HSS with COBALT Type: Blade Diameter (mm): 400 Blade Thickness (mm): 3 Bore Diameter (mm): 40

Ex GST

Number Of Teeth (No.):

Blade Best Suited for - Material Type:







Description

Made in Italy from highest quality High Speed Steel

Features

- Quality European blades suitable for cutting Mild Steels, Structural Steels, Stainless Steels, Aluminium, Alloys, Copper, Brass. Long lasting high wear resistance Can be resharpened



Product Brochure For S139B

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

BLADE SELECTION CHARTS

Coldsaw blade tooth size is determined by the size of the cross section to be cut. In general cutting thinner sections requires more teeth, thicker sections require less teeth.

To select an appropriate tooth size please refer to the table immediately below unless material to be cut is a tube, in which case refer to the larger table below.

Solid Material Blade Selection Chart

Material Diameter	Blade Diameter (mm)					
	300	315 Number	350 of teeth	400		
10mm	280	280	280	300		
20mm	160	160	200	240		
30mm	140	140	160	200		
40mm	120	120	140	140		
50mm	80	80	100	120		
60mm	×	×	80	100		

Hollow Tube Blade Selection Chart

Material Outside	Wall Thickness	Blade Diameter (mm)				
		300	315	350	400	
Diameter		Number of teeth				
20mm	3	180	180	220	240	
CASA CAASOO	3 2 1	240 300	240 320	280 350	340 400	
Valva-107 107 107	1	300	320	350	400	
40mm	4	140	140	160	180	
	3	160	160	180	200	
	3 2 1	220 300	220 320	260 350	280 400	
	'	1000	020	000	400	
50mm	5	120	140	160	180	
	4	140	160	180	200	
	5 4 3 2	160 220	180 220	200 280	220 300	
	1	300	320	350	400	
80mm	5	140	140	160	160	
ADMINISTRATION OF THE	4	160	160	180	180	
	3	180	200	200	220	
	4 3 2 1	200 280	240 300	220 320	240 360	
0.0000000000000000000000000000000000000		200	000	020	000	
100mm	5	×	140	120	140	
	5 4 3 2	×	160 200	140 180	160 180	
	3	x x	200	200	220	
	1	x	300	300	340	
120mm	5	×	x	120	140	
00000ABAS000000	4	×	×	160	160	
	3	×	×	180	180	
	5 4 3 2	×	×	200 300	220 340	
		_ ^	_ ^	300	340	