

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

HM-47B - Mill Drill - Geared & Tilting Head with Digital Readout System

Table Travel: (X) - 540mm (Y) - 205mm (Z) - 385mm Includes Digital Readout System, Dovetail Column & Stand









Back In Stock Soon

Ex GST Inc GST \$4,090.00 \$4,499.00

MODEL: HM-47B Digital Readout: 3-Axis Counter, X, Y Scales Type: Vertical Table Size (mm): 800 x 240 Column Type: Dovetail Spindle Taper - Vertical: 3MT Spindle Taper - Horizontal: ~ Longitudinal Travel (X-Axis) (mm): 540° Cross Travel (Y-Axis) (mm): 205° Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): ~ Spindle to Table (mm): 485 Spindle to Table (mm): 485 Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 6 (95 - 1650) Spi	ORDER CODE:	M140D
Type: Vertical Table Size (mm): 800 x 240 Column Type: Dovetail Spindle Taper - Vertical: 3MT Spindle Taper - Horizontal: ~ Longitudinal Travel (X-Axis) (mm): 540* Cross Travel (Y-Axis) (mm): 205* Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): ~ Spindle to Table (mm): 485 Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Cross (Y-Axis) (mm/mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) ~ (mm/min): 14 Work Table Load Capacity (kg): <td></td> <td></td>		
Table Size (mm): 800 x 240 Column Type: Dovetail Spindle Taper - Vertical: 3MT Spindle Taper - Horizontal: ~ Longitudinal Travel (X-Axis) (mm): 540° Cross Travel (Y-Axis) (mm): 205° Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): - Spindle to Table (mm): 485 Spindle to Base: - Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Vertical (X-Axis) Optional (mm/min): Power Feed - Vertical (Z-Axis) ~ (mm/min): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Horizontal (No./ rpm): 6 (95 - 1650) <td< td=""><td>Digital Readout:</td><td>3-Axis Counter, X, Y Scales</td></td<>	Digital Readout:	3-Axis Counter, X, Y Scales
Column Type: Dovetail Spindle Taper - Vertical: 3MT Spindle Taper - Horizontal: ~ Longitudinal Travel (X-Axis) (mm): 540° Cross Travel (Y-Axis) (mm): 205° Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): - Spindle to Table (mm): 485 Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Horizontal (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal Spindle (kW / hp):	Type:	Vertical
Spindle Taper - Vertical: 3MT Spindle Taper - Horizontal: ~ Longitudinal Travel (X-Axis) (mm): 540° Cross Travel (Y-Axis) (mm): 205° Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): ~ Spindle to Table (mm): 485 Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Horizontal (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal Spindle (kW / hp): ~ Motor Power - Horizonta	Table Size (mm):	800 x 240
Spindle Taper - Horizontal: ~ Longitudinal Travel (X-Axis) (mm): 540° Cross Travel (Y-Axis) (mm): 205° Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): ~ Spindle to Table (mm): 485 Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Horizontal (No./ rpm): 6 (95 - 1650) Spindle Speeds - Universal Head: ~ Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Unive	Column Type:	Dovetail
Longitudinal Travel (X-Axis) (mm): 540° Cross Travel (Y-Axis) (mm): 205° Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): - Spindle to Table (mm): 485 Spindle to Base: - Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Vertical (Z-Axis) ~ (mm/min): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): . Motor Power - Horizontal Spindle (kW / hp): . Voltage / Amperage (V / amp):	Spindle Taper - Vertical:	3MT
Cross Travel (Y-Axis) (mm): 205* Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): ~ Spindle to Table (mm): 485 Spindle to Table (mm): 120 / 75 Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) (mm/min): Optional (mm/min): Power Feed - Vertical (Z-Axis) (mm/min): ~ Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ <td>Spindle Taper - Horizontal:</td> <td>~</td>	Spindle Taper - Horizontal:	~
Vertical Travel (Z-Axis) (mm): 385 Type of Slides: Dovetail Ram Travel (mm): ~ Spindle to Table (mm): 485 Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Vertical (Z-Axis) ~ (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / hp): ~ Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp):	Longitudinal Travel (X-Axis) (mm):	540*
Type of Slides: Dovetail Ram Travel (mm): ~ Spindle to Table (mm): 485 Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): ~ Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Cross Travel (Y-Axis) (mm):	205*
Ram Travel (mm): ~ Spindle to Table (mm): 485 Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): . Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Vertical Travel (Z-Axis) (mm):	385
Spindle to Table (mm): 485 Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): ~ Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Type of Slides:	Dovetail
Spindle to Base: ~ Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): ~ Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Ram Travel (mm):	~
Spindle Travel / Diameter (mm): 120 / 75 Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Cross (Y-Axis) ~ (mm/min): ~ Power Feed - Vertical (Z-Axis) ~ (mm/min): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Spindle to Table (mm):	485
Throat Depth (max.) (mm): 265 Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Cross (Y-Axis) ~ (mm/min): ~ Power Feed - Vertical (Z-Axis) ~ (mm/min): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): - Motor Power - Horizontal Spindle (kW / hp): - Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Spindle to Base:	~
Tilting Head (Left ~ Right): ±90° Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Cross (Y-Axis) ~ (mm/min): ~ Power Feed - Vertical (Z-Axis) ~ (mm/min): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Spindle Travel / Diameter (mm):	120 / 75
Tilting Head (Forward ~ Back): Fixed Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) (mm/min): Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Throat Depth (max.) (mm):	265
Drilling Capacity (mm): 31.5 End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) (mm/min): Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Tilting Head (Left ~ Right):	±90°
End Milling Capacity (mm): 28 Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) (mm/min): Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Tilting Head (Forward ~ Back):	Fixed
Face Milling Capacity (mm): 80 Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) (mm/min): Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Drilling Capacity (mm):	31.5
Power Feed - Quill (mm/rev): ~ Power Feed - Longitudinal (X-Axis) (mm/min): Optional (mm/min): Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	End Milling Capacity (mm):	28
Power Feed - Longitudinal (X-Axis) Optional (mm/min): Power Feed - Cross (Y-Axis) ~ (mm/min): Power Feed - Vertical (Z-Axis) ~ (mm/min): Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Face Milling Capacity (mm):	80
(mm/min): ~ Power Feed - Cross (Y-Axis) (mm/min): ~ Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Power Feed - Quill (mm/rev):	~
(mm/min): Power Feed - Vertical (Z-Axis) (mm/min): ~ Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10		Optional
(mm/min): 14 Table T-Slot Size (inch / mm): 14 Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / hp): 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10		~
Work Table Load Capacity (kg): 55 Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW / hp): Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10		~
Spindle Speeds Vertical (No./ rpm): 6 (95 - 1650) Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW /	Table T-Slot Size (inch / mm):	14
Spindle Speeds Horizontal (No./ rpm): ~ Spindle Speeds - Universal Head: ~ Motor Power - Vertical Spindle (kW / 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW /	Work Table Load Capacity (kg):	55
Spindle Speeds - Universal Head: Motor Power - Vertical Spindle (kW / 1.5 / 2 hp): Motor Power - Horizontal Spindle (kW /	Spindle Speeds Vertical (No./ rpm):	6 (95 - 1650)
Motor Power - Vertical Spindle (kW / hp): Motor Power - Horizontal Spindle (kW / hp): Motor Power - Universal Head: Voltage / Amperage (V / amp): 240 / 10	Spindle Speeds Horizontal (No./ rpm):	~
Mp): Motor Power - Horizontal Spindle (kW / hp): ~ Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10	Spindle Speeds - Universal Head:	~
Mp): Motor Power - Universal Head: ~ Voltage / Amperage (V / amp): 240 / 10		1.5 / 2
Voltage / Amperage (V / amp): 240 / 10		~
	Motor Power - Universal Head:	~
Nett Weight (kg): 430	Voltage / Amperage (V / amp):	240 / 10
	Nett Weight (kg):	430

Description

This NEW HM-47B milling machines is somewhat like the HM-46B model, but with the additional benefit of a larger machine worktable with more travels, a tapping function switch to allow you to control the required depth when tapping holes, a coolant pump system with flexible hose & nozzle, a halogen work light on a flexible arm to adjust the light beam as needed and a very sturdy fabricated stand with an access panel.

The HM-47B also has a 3-Axis digital readout counter fitted with 2-Axis X & Y scales for accurate table positioning with ease, 6-speeds 95-1650rpm, gear driven head which can be tilted up to 90° either side of the vertical. This feature allows the head to be positioned in a variety of positions, allowing a whole range of milling, slotting, grooving, drilling and boring operations to be carried out on different angles. The milling head is also mounted to a vertical dovetail slide system that allows the head to maintain on the exact same centre position when raising or lowering.

The quill movement is also coupled to a digital depth counter mounted on the face of the machine for convenience and allows you to achieve accurate drilling or milling depths. Tilting the head can be also measured accurately via the digital head gauge mounted on the right side of the mill head.

Also available is an optional power feed attachment which fits to the left-hand end of the table and provides a smooth, variable speed



Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

longitudinal drive.

Features

- 3-Axis digital readout counter fitted with 2-Axis X & Y scales only
- Large 800 x 240mm ground work table with T-slots
- Powerful 2HP-240V gear driven head
- 6 spindle speeds ranging from 95-1650rpm
- 3MT spindle with 75mm diameter lockable quill
- Drilling/Milling & Tapping Functions
 Mill head tilts to ±90° from vertical with digital display
- Dovetail vertical Z-Axis with rack and pinion wind-up head
- Adjustable leadscrew nuts eliminating backlash on both axis
- Adjustable table stops with table locks
- Fine down feed handwheel operating quill feed with adjustable stop Digital depth display with zero reset for quill (Includes LR44 battery) Digital display bevel box to set head tilting (Includes AAA battery)
- Forward and reverse on/off switch
- Metric dial graduations @ 0.05mm for X & Y-Axis
- Rear slide-way cover and slide clamps on all axis
- Fixed control panel
- Coolant system with flexible hose
- Heavy duty fabricated stand with coolant & swarf tray
- * Note: X & Y travels maybe reduced due to digital readout scales and safety stops

Includes

- 3-Axis digital readout counter fitted with 2-Axis X & Y scales only
- Heavy duty fabricated stand with coolant & swarf collection tray
- Coolant system
- Halogen light
- Digital depth display
- Digital tilting head gauge
- Drill chuck & arbor
- Drill sleeve 3MT 2MT
- Face cutter & arbor
- Safety cutter guard 1/2" x 12TPI drawbar
- M12 x 1.75mm drawbar

Optional Accessories

Z-Axis scale 470mm travel - (D5220)

Specific Features









Swivel Head - 45 Degrees Left or Right 45 Degrees To Right

Mill Head Close Up

Front View



Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au



Left View



Digital Readout System



Spindle Speed Controls



Control Panel



Quill Depth Stop Guage



Digital Readout on Quill Depth



Quill Feed Handle



Fine Quill Feed Hand Wheel



Tilting Head Scale



Milling Cutter



Swivel Safety Guard



Large Ground Work Table with T Slots



Table Limit Switches



Table Feed Hand Wheel



Rack and Pinion Wind Up Head



2HP 240V Motor



Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au



SPINDLE SPEEDS RPM			
	1	2	3
L	95	180	300
н	570	1000	1650

Main Isolation Switch

Speed Chart

Recommended Accessories

C0965

Clamp Kit 58 piece - Workshop Series

K150

Mill-Drill Accessory Package Deal - Imperial Cutters

K151

Mill-Drill Accessory Package Deal - Metric Cutters

C922B

Collet & Chuck Set - 8 Piece









C926

Collet & Chuck Set - 20 Piece

M3301

Metric HSS Slot Drill & End Mill Set - 10 Piece

M3321

Imperial HSS Slot Drill & End Mill Set - 10 Piece

M182

Precision Boring Head Kit











Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Product Brochure For M140D

M192 Boring Head Shank

M180 Boring Bar Set - 9 piece

M250 Parallel Set - 8 Piece

M530 Universal Milling Kit - 4 Piece









M562 Face Mill Arbor

M515 Face Mill 45° - Super High-Rake

L065 KYOCERA Carbide Inserts -Milling

M528 Face Mill 90° - Positive Rake










M529 Face Mill 90° - Positive Rake

L066 KYOCERA Carbide Inserts -Milling

V004 Cast Iron Vee Block

V105 Vertex K-Type Milling Vice











Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Product Brochure For M140D

R006

Vertex Rotary Table

M230

Power Feed Unit

M240

Transformer

P235

Coolant Pump & Tank









S090A

Soluble Metal Cutting Fluid - 1

S090

Soluble Metal Cutting Fluid - 5

L341

Fitting and Machining Technical


L3455

Professional Sheet Metal Fabrication Book









L300

Magnetic Swarf Remover

M9991

Magnetic Floor Sweeper

M800

Rubber Mat - Anti-Fatigue

M805

Rubber Mat - Anti-Fatigue











Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Product Brochure For M140D

O000

SpillFix Universal Organic Absorbent



Natural Zeolite Absorbent



Rust & Corrosion Preventive - Penetrant & Lubrication

O042

General Purpose Lubricant & Corrosion Inhibitor









O040

Rust & Corrosion Preventive - Penetrant & Lubrication

O044

Rust & Corrosion Preventive - Penetrant & Lubrication



