

**Product Brochure For S156** 

## S156 - HSS Cold Saw Blade

Ø275mm / 32mm Bore - 140T



Sydney:	(02)	9890	9111
Brisbane:	(07)	3715	2200
Melbourne:	(03)	9212	4422
Perth:	(08)	9373	9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Ex GST	Inc GST	
\$170.00	\$187.00	

ORDER CODE:	S156
Туре:	HSS
Blade Diameter (mm):	275
Blade Thickness (mm):	2.5
Bore Diameter (mm):	32
Number Of Teeth (No.):	140
Blade Best Suited for - Material Type:	Mild Steel



#### Description

Made in Italy from highest quality High Speed Steel

#### Features

- Quality European blades suitable for cutting Mild Steels, Structural Steels, Stainless Steels, Aluminium, Alloys, Copper, Brass. Long lasting high wear resistance Can be resharpened •
- •



Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

Product Brochure For S156

sales@machineryhouse.com.au www.machineryhouse.com.au

# **BLADE SELECTION CHARTS**

Coldsaw blade tooth size is determined by the size of the cross section to be cut. In general cutting thinner sections requires more teeth, thicker sections require less teeth.

To select an appropriate tooth size please refer to the table immediately below unless material to be cut is a tube, in which case refer to the larger table below.

### **Solid Material Blade Selection Chart**

		Blade Diar	neter (mm)	
Material Diameter	300	315 Number	350 of teeth	400
10mm	280	280	280	300
20mm	160	160	200	240
30mm	140	140	160	200
40mm	120	120	140	140
50mm	80	80	100	120
60mm	x	x	80	100

### Hollow Tube Blade Selection Chart

Material		Blade Diameter (mm)			
Outside	Wall Thickness	300	315	350	400
Diameter			Number	of teeth	
20mm	3 2 1	180 240	180 240	220 280	240 340
	1	300	320	350	400
40mm	4 3 2 1	140 160 220 300	140 160 220 320	160 180 260 350	180 200 280 400
50mm	5 4 3 2 1	120 140 160 220 300	140 160 180 220 320	160 180 200 280 350	180 200 220 300 400
80mm	5 4 3 2 1	140 160 180 200 280	140 160 200 240 300	160 180 200 220 320	160 180 220 240 360
100mm	5 4 3 2 1	× × × × ×	140 160 200 220 300	120 140 180 200 300	140 160 180 220 340
120mm	5 4 3 2 1	× × × × ×	× × × × × × ×	120 160 180 200 300	140 160 180 220 340