

SB36-3M - MIG Torch - 3 Metre

3 Metre
 Suits 335-400 Amp



Special Order

Ex GST
\$160.00

Inc GST
\$176.00

| | |
|--------------------------------|----------------|
| ORDER CODE: | W572 |
| Part Number: | SB36-3M |
| Type: | MIG Torch |
| Amperage (amp): | 300 |
| Electrical Pin Connector: | ~ |
| Duty Cycle Rating: CO2: | 60% @ 300amp |
| Duty Cycle Rating: Mixed Gas: | 60% @ 270amp |
| Includes U-Groove Roller (mm): | ~ |
| Wire Size Capability (mm): | 0.6 - 1.2 |
| Torch Connector (Type): | Euro Connector |



Description

Suregrip Series
 SB36 MIG Torch

Features

- 300A AIR COOLED MIG WELDING TORCH
- Rating:300A CO²
- 270A mixed gas
- EN60974-7 @ 60% duty cycle
- 0.8 to 1.2mm wires



Unimig
Suregrip Series

Consumable parts

All wear and spare parts are manufactured to the same specification as the OEM and are fully interchangeable.

Hanger Hook

A "plug and play" option, they encourage the operator to hang the torch off the ground where it is easy to locate.

Medium Ergo Trigger Assembly

Rapid field servicing ensured by a simple "plug and play" system. Switches can be exchanged in 5 seconds without the use of tools.

Knuckle Joint and Cable Support

Small movements of the handle and neck are possible independent of the cable assembly. A moulded polymer cable support increases flexibility and electrode support.



Spring Pins

Fitted with unbreakable spring loaded gun plug body pins.

Rear Cable Support

Extra length cable support systems ensure smooth and consistent wire feed at any angle.

Swan Necks

Manufactured to the same specification as the OEM.



Ergo Handle

A patented screwless design combines the ultimate in balance, positioning and ergonomics. Torch handles disassemble in 5 seconds for rapid fault analysis. Top and bottom handle soft grips ensure all day welder comfort.

Hyperflex Cable Systems

Air cooled cable assemblies offer outstanding flexibility with the highest heat and abrasion resistance of any known cable. The outer jacket is constructed from cross-linked polymers providing a tear proof outer with a burn threshold of 375°C.



Gun Plug Housing

Tough and damage resistant, housings and nuts are formed in robust glass-reinforced polymers encasing all conductive parts in accordance with EN60974-7.

Product Brochure For W572

Recommended Accessories

W10350
 MIG Hand Rest Glide Kit



W10362
 Magnetic MIG Torch Rest



W546
 10 x 0.6mm Contact Tips - Steel



W548
 10 x 0.8mm Contact Tips - Steel



W549
 10 x 0.9mm Contact Tips - Steel



W550
 10 x 1.0mm Contact Tips - Steel



W552
 10 x 1.2mm Contact Tips - Steel



W549A
 10 x 0.9mm Contact Tips - Aluminium



Product Brochure For W572

W550A
 10 x 1.0mm Contact Tips -
 Aluminium



W552A
 10 x 1.2mm Contact Tips -
 Aluminium



W539
 0.6-0.8mm Blue Steel Liner



W538
 1.0-1.2mm Red Steel Liner



W567
 1.0-1.2mm Red Aluminium Liner



W564
 2 x Conical Nozzles



W576
 2 x Gas Diffusers



W568
 Swan Neck Assembly



W571
 MIG Torch - 4 Metre



W183
 MIG/TIG/STICK WELDER



W187
 MIG/TIG/STICK WELDER



W252
 MIG WELDER



Product Brochure For W572

sales@machineryhouse.com.au
www.machineryhouse.com.au

W253
MIG WELDER



W253A
MIG WELDER

