

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au

www.machineryhouse.com.au

Product Brochure For P6095

P6095 - 14 x 25mm Slotted Punch

Hi -Grade Tool Steel Imported From Japan Ø30mm Locating Diameter



Ex GST	Inc GST
\$120.00	\$132.00

ORDER CODE:	P6095
Shape - Type:	Slotted Punch - 0P1
Square or Slot Hole Size (W x L) (mm):	14 x 25
Punch Locating Diameter x Length (mm):	Ø30 x 70mm
Die Outside Body Diameter x Height (mm):	~





Description

Punch and Dies are Manufactured by Sunrise in Taiwan using Hi -Grade Tool Steel imported from Japan. The manufacturing process involves machining via hi tech CNC machines lathes & mills, vacuum heat treatment with multiple tempering at high temperatures before a final quality inspection/testing process all of which ensures an accurate, precise, durable & stable product.

Features

- PLEASE NOTE FOLLOWING RECOMMENDATIONS WHEN SELECTING DIE CLEARANCE: •
- Material Thickness 2 ~ 4mm = Die Clearance 0.2mm
- Material Thickness 4 ~ 9.5mm = Die Clearance 0.7mm
- Material Thickness 10 ~ 14.5mm = Die Clearance 1.2mm
- Material Thickness 15 ~ 19.5mm = Die Clearance 1.7mm Material Thickness 20 ~ 24mm = Die Clearance 2.2mm

Optional Accessories

- Please Note: Slotted punch requires a sleeve to fit on current Sunrise machines
- Models IW-45MQ. IW-45K, IW-60H requires (PP630A)
- Models IW-60S/SD, IW-80S/SD IW-100S/SD, IW-125S/SD, IW-165S/SD requires (PP630) •



Product Brochure For P6095

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Specific Features



Top View

Recommended Accessories

PP630A QUICK CHANGE ADAPTOR 30MM PP630 QUICK CHANGE ADAPTOR 30MM



PP0016 DIE RING SPACER







