

Product Brochure For L765

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Inc GST

L765 - Lathe - Boring Ring for Chuck Soft Jaws

Ø5" (Ø127mm)



| \$24 | -0.00 | \$264.00 | |
|-------------------|-------|----------|------|
| ORDER CODE: | | | L765 |
| Size (inch): | | | 5" |
| A (mm): | | | 12 |
| B (mm): | | | 140 |
| C (mm): | | | 60 |
| D (mm): | | | 12 |
| E (mm): | | | 28 |
| F (mm): | | | 9 |
| G (mm): | | | 13 |
| Nett Weight (kg): | | | 1.1 |

Ex GST









Description

To suit any lathe that uses soft jaws. The ring is used to hold the jaws in place so the the soft jaws can be machined to a certain size.

Material SCM440

Features

- · Maintains a high level of accuracy
- The operation process is as follows
- 1. Set the jaws to the correct position that will allow the diameter required to be machined.
- 2. Adjust the boring ring so that the pins are located in the recessed hols in the jaws.
- 3. Lock the chuck so that the boring ring is clamped.
- 4. Machine the jaws to the required size.
- 5. Unlock the chuck and remove the boring ring
- 6. If the process is followed the jaws will repeat the accuracy each time the chuck is closed onto the work piece.