

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au

www.machineryhouse.com.au

Product Brochure For S535

SG-420 - Hydraulic Guillotine

1300 x 2mm Mild Steel Shearing Capacity Manual Backgauge



Ex GST	Inc GST
\$6.990.00	\$7.689.00

. ,	
ORDER CODE:	S535
MODEL:	SG-420
Shearing Capacity - Mild Steel (mm):	2
Shearing Capacity - Stainless Steel (mm):	0.9
Shearing Length (mm):	1300
NC Control (Type):	~
Backgauge (Type):	Manual
Backgauge Travel (mm):	550
Pneumatic Sheet Supports:	~
Quick Action Blade Clearance Adjustment:	~
Strokes / min (SPM):	~
Blade Angle (deg):	~
Throat Depth (mm):	~
Motor Power (kW / hp):	2.2/3
Voltage / Amperage (V / amp):	240 / 15
Floor Space Requirements (L x W x H) (mm):	1750 x 1475 x 1110
Nett Weight (kg):	560



Description

The SG-420 compact hydraulic guillotine is a machine that should be in every sheet metal fabrication shop. This 1300mm guillotine will easily cut 2mm mild steel over its full length and operates on 240 volt 15 amp single phase power. The SG-420 comes complete with an adjustable back gauge for precise repeatability. It also comes standard with a squaring arm and front sheet supports.

Features

- 1300mm x 2mm cutting capacity
- 2.2kW / 3hp 240V motor
- 880mm work table height
- Adjustable manual backgauge Roving foot pedal control
- Blades made from 9CrSi material suitable for cutting stainless steel
- Safety photo electric rear guarding with 3 beams Safety reset rear guarding button mounted to back of electrical box •
- •
- Front arm supports & squaring glide Mild steel capacity is rated on hot rolled material with 250MPA
- Pre-Commissioning: 1. Guillotine is run & tested prior delivery 2. Hydraulic oil is included with machine



Product Brochure For S535

Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Specific Features





Front View



Squaring Guide



Control Panel



Front Sheet Supports



Material Clamp Bar Guard





Rear Left View



Rear Back Gauge



Top Beam Oil Access



Isolation Switch and Rear Guard Reset Button Shown with Optional Ball Transfer Tables



Rear Right View

Right View



3 x Rear Safety Photoelectric Sensors Safety Photoelectric Sensor





Emergency Stop On Roving Foot Pedal Roving Foot Pedal



Product Brochure For S535


Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Recommended Accessories

S9981

1320mm Sheet Metal Guillotine Blade Set - 9CrSi M800 Rubber Mat - Anti-Fatigue M805 Rubber Mat - Anti-Fatigue O000 SpillFix Universal Organic Absorbent









O000A Natural Zeolite Absorbent

O043 Rust & Corrosion Preventive -Penetrant & Lubrication

O042 General Purpose Lubricant & Corrosion Inhibitor

O040 Rust & Corrosion Preventive -Penetrant & Lubrication











Sydney: (02) 9890 9111 Brisbane: (07) 3715 2200 Melbourne: (03) 9212 4422 Perth: (08) 9373 9999

sales@machineryhouse.com.au www.machineryhouse.com.au

Product Brochure For S535

O044

Rust & Corrosion Preventive -Penetrant & Lubrication O004 Superdraulic 46 Hydraulic Oil



